

Thank you for your order!

# Instructions

## SmoothGRIP

### 1. AREA

- a. Choose a smooth surface area for your decals.
- b. Any hard surfaces including terrazzo, finished concrete, wood or vinyl tiles are fine.
- c. Do not install over grout lines or cracks.
- d. If your area has floor wax applied, make sure it is in good condition (no peeling/flaking).



### 2. CUT

- a. Use sharp scissors for cutting out the decals.

### 3. CLEAN

- a. Thoroughly clean the floor area chosen.
- b. Please ensure that no chemical residue is left on the floor from the cleaning.
- c. To ensure the floor is dry, please wait 24 hours before beginning the installation.



### 4. PLACE

- a. Craft the entire layout by placing the (unpeeled) decals on the ground to visualize the path before installing.



### 5. PEEL

- a. **Small sticker: 1 Person**
  - i. Peel the backing off the decal and lay it on the surface, press down from the middle of the sticker, outwards. Ensure the entire sticker including the edges have adhered to the surface.
- b. **Large sticker: 2 Person**
  - i. Peel the backing off about 2 inches from one side of the decal.
  - ii. While keeping that side pulled taut, apply it on the surface.



- iii. You can always peel away a try again to get it straight.
  - iv. Once a straight edge has been applied, one person slowly pulls the loose backing further off exposing more of the sticker underside.
  - v. The other person uses a squeegee or credit card to push down on the newly exposed sticker from the middle outwards.
  - vi. Work slowly and avoid wrinkles by keeping the decal pulled tautly.
- c. Ensure the entire sticker including the edges have adhered to the surface.

## 6. SMOOTH

- a. Use a cloth, a squeegee, or any soft material to smooth out any wrinkles and push out air bubbles. You can use a pin or a sharp knife to pop stubborn air bubbles.



## 7. LONGEVITY

- a. After installation, please allow a minimum of 24 hours before applying wax over the adhesive decals
- b. We recommend applying a minimum of 6-7 layers of wax over the area once installed for an affordable and permanent application. The more layers of wax, the better protected your path will be.
- c. Conventional waxes are usually compatible with vinyl decals - as long as they are safe for linoleum or vinyl tiles. If you are unsure, please test compatibility on a small decal before applying over the entire path.
- d. Some floor coatings/sealers are not designed for vinyl floors and cannot be used on vinyl decals. Please contact the manufacturer of your floor products for compatibility.
- e. Once applied, the wax will protect your decals from peeling and scuffing for many years.
- f. Machine cleaners can be used and the top 1-2 layers of wax can be stripped/reapplied anytime.
- g. **If you don't apply wax over the decals, machine cleaners or floor scrubbers of any kind cannot be used as they will remove the decals from the floor.**
- h. Regular manual cleaning and mopping is no problem.



If you have any questions please contact us!

Email: [jean@jump2math.ca](mailto:jean@jump2math.ca)  
 Toronto: 416-206-2396  
 New York: 347-704-0580

